



IMC MOTOR CO. LTD.

DIESEL WELDER GENERATOR



- **High performance**
- **Low noise**
- **Easy maintenance**
- **High quality**
- **Compact design**

	MODEL	AWD160 (E)	
DC WELDER	Max. Current (A)	190	
	Voltage Rated (V)	25	
	Current Range (A)	80 - 190	
	Duty Cycle	60%	
	Applicate Electrode Diameter (mm)	2.0 - 4.0	
	Rated Revolution (rpm)	3600	
	No- Load Voltage (V)	50	
	Welding Operating Voltage (V)	17 -53	
	Frequency (Hz)	50	60
	AC GENERATOR	Rated Output (KVA)	3.0
Max. Output (KVA)		3.3	
Rated Voltage (V)		*110~120, 220~240 (110/220, 120/240 - For 60Hz Only)	
Speed (rpm)		3000	3600
Power Factor		1.0	
Phase		Single	
ENGINE	Type	4-Cycle, Air-Cooled Diesel Engine	
	Displacement (cc)	418	
	Max. Output (KW / rpm)	5.7	6.3
	Prective System of Low Pressure	Standard	
	Starting System	Recoil / Electric (E)	
OTHERS	Fuel Tank Capacity (ℓ)	12.5	
	Dimensions (mm)	775 x 495 x 625	
	Dry Weight (kg)	108 (※112)	
	4-wheels Kit	Optional	

Note : (※) : Electric starter

Distributor :

